

IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application. An identifier indicating the status of each claim is provided.

Listing of Claims

1-6. (Canceled)

7. (Currently Amended) An information transmission apparatus for transmitting information through a first transmission path, comprising:

receiving means for receiving a broadcasting signal from a second transmission path;

demodulation means for demodulating the signal received by the receiving means;

and

modulation means for modulating the signal demodulated by the demodulation means,

wherein the modulation means includes network information replacement means for replacing network information demodulated by the demodulation means with information for the first transmission path,

wherein the information for the first transmission path includes a first delivery system descriptor and the network information includes a second delivery system descriptor,

wherein said first delivery system descriptor length and said second delivery system descriptor length are set in accordance with a transport stream descriptor length has a length equal to said second delivery system descriptor,

wherein service identifiers of network information that are not retransmitted are deleted and placeholder data ~~for~~ that has the same length of the deleted service identifiers is added, and

wherein a plurality of service list descriptor is repeatedly descriptors are appended to a transport stream identifier in accordance with the length of [[a]] said transport stream descriptor for identifying a new or previous transmission.

8. (Canceled)

9. (Currently Amended) An apparatus according to claim 7, ~~characterized in~~ that wherein the network information replacement means includes network information extraction means for extracting the network information of the signal demodulated by the demodulation means, network information conversion means for converting the network information extracted by the network information extraction means in compliance with a network to which the network information is to be retransmitted, and network information reinjection means for replacing the network information of the signal demodulated by the modulation means with the information for the first transmission path, using the network information converted by the network information conversion means as the information for the first transmission path.

10. (Currently Amended) An apparatus according to claim 9, ~~characterized in~~
~~that wherein~~ the first transmission path is a cable television channel, and the second transmission
path is a satellite broadcasting channel.

11. (Currently Amended) An apparatus according to claim 10, ~~characterized~~
~~in that wherein~~ the network information replacement means extracts, from a signal from an
arbitrary satellite system network among a plurality of satellite system networks, a network
information item concerning the arbitrary satellite system network, and a network information
item concerning another satellite system network, by means of the network information
extraction means, converts respectively the network information items into network information
items that comply with a network to which the network information items are to be retransmitted,
and replaces the network information of the signal demodulated by the demodulation means with
information for a cable, using the network information items converted by the network
information conversion means as the information for the cable.

12. (Currently Amended) An information transmission method for
transmitting information through a first transmission path, said method comprising:
a receiving step of receiving a broadcasting signal from a second transmission
path;
a demodulation step of demodulating the signal received in the receiving step; and
a modulation step of modulating the signal demodulated by the demodulation
step,

wherein the modulation step includes a step of replacing network information demodulated by the demodulation step with information for the first transmission path,

wherein the information for the first transmission path includes a first delivery system descriptor and the network information includes a second delivery system descriptor,

wherein said first delivery system descriptor length and said second delivery system descriptor length are set in accordance with a transport stream descriptor length has a length equal to said second delivery system descriptor,

wherein service identifiers of network information that are not retransmitted are deleted and placeholder data for that has the same length of the deleted service identifiers is added, and

wherein a plurality of service list descriptor is repeatedly descriptors are appended to a transport stream identifier in accordance with the length of [[a]] said transport stream descriptor for identifying a new or previous transmission.

13. (Canceled)

14. (Currently Amended) A method according to claim 12, ~~characterized in that~~ wherein the network information replacement step includes a network information extraction step of extracting the network information of the signal demodulated in the demodulation step, a network information conversion step of converting the network information extracted in the network information extraction step so as to comply with a network to which the network

information is to be retransmitted, and a network information reinsertion step of replacing the network information of the signal demodulated in the modulation step with the information for the first transmission path, using the network information converted in the network information conversion step as the information for the first transmission path.

15. (Currently Amended) A method according to claim 12, ~~characterized in that~~ wherein the first transmission path is a cable television channel, and the second transmission path is a satellite broadcasting channel.

16. (Currently Amended) A method according to claim 15, ~~characterized in that~~ wherein in the network information replacement step, from a signal from an arbitrary satellite system network among a plurality of satellite system networks, a network information item concerning the arbitrary satellite system network and a network information item concerning another satellite system network are extracted,

in the network information conversion step, the network information items extracted in the network information extraction step are converted into network information items that comply with a network to which the network information items are to be retransmitted, and

in the network information reinsertion step, the network information of the signal demodulated in the demodulation step with information for a cable, using the network information items converted in the network information conversion step as the information for the cable.

17-18. (Canceled)